


AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. (original) A treated particulate inorganic solid composition comprising:
 - (a) a particulate inorganic solid; and
 - (b) an organophosphinic compound having the formula:



wherein R_1 is a organic group having from 2 to 22 carbon atoms, and
 R_2 is hydrogen, or an organic group having from 2 to 22 carbon atoms, and
 M is hydrogen, ammonium, organoammonium or a metal ion.

2. (original) The treated particulate inorganic solid composition of claim 1, wherein the particulate inorganic solid is selected from the group consisting of kaolin, talc, calcium carbonate, zinc oxide and mica.

3. (original) The treated particulate inorganic solid composition of claim 1, wherein the particulate inorganic solid is titanium dioxide.

4. (currently amended) The treated particulate inorganic solid composition of claim 1, wherein the particulate inorganic solid is treated with a compound selected from the group consisting of polyalcohols, alkanolamines, inorganic phosphates and mixtures thereof prior to addition of the organophosphinic compound, or the treated particulate inorganic solid composition is further treated with a compound selected from

the group consisting of polyalcohols, alkanolamines, inorganic phosphates and mixtures thereof subsequent to addition of the organophosphinic compound.

5. (original) The treated particulate inorganic solid composition of claim 1, wherein said composition further comprises an inorganic oxide.

6. (original) The treated particulate inorganic solid composition of claim 5, wherein said inorganic oxide is selected from the group consisting of silicon dioxide, zirconium oxide and aluminum oxide.

7. (original) The treated particulate inorganic solid composition of claim 1, wherein R_1 is hexyl-, octyl-, isooctyl- or 2-ethylhexyl-.

8. (original) The treated particulate inorganic solid composition of claim 1, wherein the organophosphinic compound is present in the amount from about 0.1 percent to about 5 percent by weight of the particulate inorganic solid, based on the weight of the particulate inorganic solid prior to treating the particulate inorganic solid with the organophosphinic compound.

9. (original) The treated particulate inorganic solid composition of claim 1, wherein the organophosphinic compound is present in the amount from about 5 percent to about 30 percent by weight of the particulate inorganic solid, based on the weight of the particulate inorganic solid prior to treating the particulate inorganic solid with the organophosphinic compound.

10. (original) A polymer matrix comprised of a polymer and the treated particulate inorganic solid composition of claim 1.


11. (original) The polymer matrix of claim 10, wherein the polymer is polyethylene.

12. (original) The polymer matrix of claim 11, wherein the amount of the treated particulate inorganic solid composition is from about 50 percent to about 85 percent by weight of the polymer matrix, based on the weight of the polymer matrix.

13. (original) The polymer matrix of claim 12, wherein the particulate inorganic solid is titanium dioxide.

14. (original) A method for preparing a treated particulate inorganic solid composition, wherein said method comprises the steps of: (i) filtering a slurry, said

slurry comprising a particulate inorganic solid; and (ii) combining said particulate inorganic solid after said filtering with an organophosphinic compound, wherein said organophosphinic compound has a formula of:




wherein R_1 is a organic group having from 2 to 22 carbon atoms, and
 R_2 is hydrogen, or an organic group having from 2 to 22 carbon atoms, and
 M is hydrogen, ammonium, organoammonium or a metal ion.

15. (original) The method according to claim 14, wherein the particulate inorganic solid has been treated with the organophosphinic compound prior to a drying stage.

16. (original) The method according to claim 14, wherein the particulate inorganic solid has been treated with the organophosphinic compound during a milling stage.

17. (original) The method according to claim 14, wherein the particulate inorganic solid has been treated with the organophosphinic compound when the particulate inorganic solid is in the form of a filter cake.

18. (original) A method for preparing a treated particulate inorganic solid, comprising combining a dry particulate inorganic solid and an organophosphinic compound, wherein said organophosphinic compound has a formula of:



wherein R_1 is a organic group having from 2 to 22 carbon atoms, and

R_2 is hydrogen, or an organic group having from 2 to 22 carbon atoms, and

M is hydrogen, ammonium, organoammonium or a metal ion.

19. (original) The method according to claim 18, wherein the particulate inorganic solid has been treated with the organophosphinic compound during a micronization stage.

20. (original) The method according to claim 19, wherein the particulate inorganic solid is titanium dioxide.

21. (original) The method according to claim 19, wherein the particulate inorganic solid is titanium dioxide, and R_1 is hexyl-, octyl-, iso octyl- or 2-ethylhexyl-.